

Abrasive paper
PS 21 F


Close coating, tear-resistant backing and high-quality, self-sharpening Alumina zirconia grain for a long service life and high grinding performance particularly on stainless steel surfaces

Available grits:

16	120 ■	500 ■
24	150 ■	600
30	180 ■	800
36 ■	220 ■	1000
40 ■	240 ■	1200
50	280 ■	1500
60 ■	320 ■	2000
80 ■	360	
100 ■	400 ■	

Applications:

Stainless steel	●
Metal	●
Steel	●



Bonding agent
Resin
Grain
Al. zirconia/Al. oxide
Coating
Close
Backing
F

All sizes and minimum purchasing quantities available on request

Abrasive paper, ANTISTATIC
PS 22 F ACT



Close coat for maximum stock removal and uniform scratch pattern regarding surface treatment of hard, low-content woods. ACT and antistatic properties prevent premature clogging

Available grits:

16	120 ■	500
24 ■	150 ■	600
30 ■	180 ■	800
36	220 ■	1000
40 ■	240 ■	1200
50 ■	280 ■	1500
60 ■	320 ■	2000
80 ■	360 ■	
100 ■	400 ■	

Applications:

Wood	●
Metal	○
NF metals	○



Bonding agent
Resin
Grain
Aluminium oxide
Coating
Close
Backing
F

All sizes and minimum purchasing quantities available on request

Abrasive paper, ANTISTATIC
PS 24 F ACT



Close coating, tear-resistant backing with tough SiC for varnished and primed surfaces in the wood processing industry, especially furniture industry

Available grits:

16	120 ■	500 ■
24	150 ■	600 ■
30	180 ■	800 ■
36	220 ■	1000
40	240 ■	1200
50	280 ■	1500
60	320 ■	2000
80 ■	360 ■	
100	400 ■	

Applications:

Paint/Varnish/Filler	●
Wood	○
Plastic	○



Bonding agent
Resin
Grain
SiC
Coating
Close
Backing
F

All sizes and minimum purchasing quantities available on request

Abrasive paper, ANTISTATIC
PS 29 F ACT



Abrasive belt with outstanding service life. Open coat, antistatic properties as well as ACT prevent premature clogging. The abrasive paper is particularly suitable for processing soft and high-resin woods

Available grits:

16	120 ■	500
24	150 ■	600
30	180 ■	800
36	220 ■	1000
40 ■	240 ■	1200
50 ■	280 ■	1500
60 ■	320 ■	2000
80 ■	360	
100 ■	400 ■	

Applications:

Wood	●
------	---



Bonding agent
Resin
Grain
Aluminium oxide
Coating
Open
Backing
F

All sizes and minimum purchasing quantities available on request

Other sizes available on request.