

**Abrasive paper** 

**PS 21 F** 



Close coating, tear-resistant backing and high-quality, self-sharpening Alumina zirconia grain for a long service life and high grinding performance particularly on stainless steel surfaces

Available gri	ts:	
16	120 ■	500 ■
24	150 ■	600
30	180 ■	800
36 ■	220 ■	1000
40 ■	240 ■	1200
50	280 ■	1500
60 ■	320 ■	2000
80 ■	360	
100 ■	400 ■	

Applications:	
Stainless steel	•
Metal	•
Steel	•



All sizes and minimum purchasing quantities available on request

Abrasive paper, ANTISTATIC


PS 24 F ACT



Close coating, tear-resistant backing with tough SiC for varnished and primed surfaces in the wood processing industry, especially furniture industry

Available gri	ts:	
16	120 ■	500 ■
24	150 ■	600 ■
30	180 ■	800 ■
36	220 ■	1000
40	240 ■	1200
50	280 ■	1500
60	320 ■	2000
80 ■	360 ■	
100	400 ■	

Metal	•
Paint/Varnish/Filler	•
Wood	0
Plastic	0



All sizes and minimum purchasing quantities available on request

Abrasive paper, ANTISTATIC

PS 29 F ACT



Abrasive belt with outstanding service life. Open coating, antistatic properties as well as ACT prevent premature clogging. The abrasive paper is particularly suitable for processing soft and high-resin woods

Available gri	ts:	
16	120 ■	500
24	150 ■	600
30	180 ■	800
36	220 ■	1000
40 ■	240 ■	1200
50 ■	280 ■	1500
60 ■	320 ■	2000
80 ■	360	
100 ■	400 ■	

Vood	•
------	---



All sizes and minimum purchasing quantities available on request



# **Abrasive cloth**

**CS 310 X** 



Abrasive cloth for metal and wood working with stable cloth backing, for heavy duty with particularly long service life

Available gri	ts:	
16 ■	120 ■	500 ■
24 ■	150 ■	600 ■
30 ■	180 ■	800
36 ■	220 ■	1000
40 ■	240 ■	1200
50 ■	280 ■	1500
60 ■	320 ■	2000
80 ■	360	
100 ■	400 ■	

### Applications:

Metal	•
Wood	0
Plastic	0
Leather	0



Bonding agent
Resin
Grain
Aluminium oxide
Coating
Close
Backing
X

All sizes and minimum purchasing quantities available on request

#### **Abrasive cloth ANTISTATIC**

# **CS 311 Y ACT**



Open coated aluminium oxide on polyester cloth for calibrating and intermediate sanding in woodworking. ACT and antistatic properties prevent premature clogging

Available gr	its:	
16	120 ■	50
24	150 ■	60
30	180 ■	80
36 ■	220 ■	100
40 ■	240	120
50 ■	280	150
60 🔳	320	200

360

400

Applications:	
Wood	•
Metal	0



All sizes and minimum purchasing quantities available on request

## Abrasive cloth, multibond

**CS 409 Y** 



Extremely tear-resistant high-performance belt with high stock removal efficiency and long service life due to additional multibond, for stainless steel and high-alloy steels, multibond for cool grinding

## Available grits:

80 🔳

100 ■

16	120 ■	500
24	150	600
30	180	800
36 ■	220	1000
40 ■	240	1200
50 ■	280	1500
60 ■	320	2000
80 ■	360	
100 ■	400	

## Applications:

•
•



Bonding agent	
Resin	
Grain	
Alumina zirconia	
Coating	
Close	
Backing	
Υ	

All sizes and minimum purchasing quantities available on request