

Masonry



**For those really
tough jobs**

RN[®]

made in France

Plain Shank



TCT

PERFORMANCE

Concrete

Stone

Granite

Brick

2 cutting edges



Carbide percussion tip with semi positive profile for aggressive drilling in hard materials.

double fluted spiral



Rolled double flute provides greater dust extraction extending drill life.

shank



Parallel shank.



Masonry Drills

Masonry Drill Bits Tungsten Carbide Tipped

Tradesman quality for rotary and percussion drilling. Product packaging is colour code marked to indicate the correct plug size. Ideal for use in natural and artificial stone, masonry brickwork and concrete.

Tungsten carbide tipped for increased life. Suitable for all impact drills or rotary hammer drills fitted with a chuck.

Note: When using the rotary hammer, ensure you set the tool to impact mode.



Size	Plug Colour	OA Length	Shank Size	Pieces	Item #	Barcode	Price
3.0	Yellow	60			140H00030	9311744090013	
4.0		75			140H00040	9311744090020	
5.0	White	85			140H00050	9311744090037	
5.0		150			143H00050	9311744091010	
5.5	Red	95			140H00055	9311744090044	
5.5		150			143H00055	9311744091027	
6.0		100			140H00060	9311744090051	
6.0		150			143H00060	9311744091034	
6.5	Green	100			140H00065	9311744090068	
6.5		150			143H00065	9311744091041	
6.5		400			145H00065	9311744092017	
7.0		100			140H00070	9311744090075	
7.0		150			143H00070	9311744091058	
8.0	Blue	120			140H00080	9311744090082	
8.0		150			143H00080	9311744091065	
8.0		400			145H00080	9311744092024	
9.0		120			140H00090	9311744090099	
10.0	Orange	120			140H00100	9311744090105	
10.0		150			143H00100	9311744091072	
10.0		400			145H00100	9311744092031	
11.0	Grey	150			143H00110	9311744091089	
12.0		150			143H00120	9311744091096	
13.0		150	10.0		143H00130	9311744091102	
13.0		400	10.0		145H00130	9311744092048	
14.0		150	10.0		143H00140	9311744091119	
16.0	Black	150	12.7		143H00160	9311744091126	
16.0		400	12.7		145H00160	9311744092055	
20.0		160	12.7		143H00200	9311744091133	
20.0		400	12.7		145H00200	9311744092062	
22.0		160	12.7		143H00220	9311744091140	
22.0		400	12.7		145H00220	9311744092079	
25.0		160	12.7		143H00250	9311744091157	
25.0		400	12.7		145H00250	9311744092086	

Merchandiser

Quantity	Configuration	Pieces	Item #
10 each	(SF) 5.5, 6.5mm	86	140HMR86
5 each	(SB) 5.5, 6.5, 10.0mm		
	(SF) 3.0, 4.0, 5.0, 6.0, 7.0, 8.0, 10.0mm		
2 each	(SB) 5.0, 6.0, 7.0, 8.0, 11.0, 12.0, 13.0, 16.0mm		



MRY86

Prices exclude GST

(SF) - Standard Fixing (SB) - Single Brick (DB) - Double Brick
 **Please contact your Sutton Tools representative when ordering merchandisers

made
in
France

Plain
Shank

PERFORMANCE

Glass 

Tile 

Cement Sheet 

4 edge tip



Tungsten Carbide Tipped.
4 edge spear design.
Shaves rather than cuts.

shank



Parallel shank.

8.0mm

Glass & Tile Drill



Tungsten carbide tipped
for drilling glass & tile

RN

Glass & Tile Drills

Glass & Tile Drill Bits

Sometimes called Spear Point Drills. Precision ground carbide tipped for exact drilling. High tempered brazed carbide tip. This design is intended to produce clean holes in ceramic tiles, porcelain and glass.

NOTE: not suitable for toughened glass. These drill bits need to be used at a slow speed, non impact, with suitable coolant.



Size	Item #	Barcode	Price
3.0	148H01250	9311744093014	
4.0	148H01562	9311744093045	
5.0	148H01875	9311744093021	
6.0	148H02500	9311744093038	
6.5	148H02559	9311744435012	
8.0	7301148	9312621738059	
10.0	7301157	9312621738066	
12.0	7301175	9312621738073	

made
in
China

Hollow
Shank

PERFORMANCE

Sandstone	
Terracotta	
Ceramic	
Glass (not safety)	
Glazed Tile	



tip

Diamond resin bonded.
For wet drilling only.



shank

Hollow core allows
internal coolant.

Diamond Core Bits

Diamond Core Bits

Diamond Tile Core bits have diamond encrusting to cut through glazed and polished porcelain, sandstone, terracotta and ceramics.

Suitable for tiling, plumbing, electrical, building trade and DIY handy person applications.

- Now cuts to $\pm 0.2\text{mm}$.

Helpful Hints

- This product is for wet drilling only
- Always keep the drilling area wet
- Always use a slow continuous speed
- Never use the power tool on hammer setting
- To avoid drill slipping start drill at a 45° angle, and gradually straighten the power tool
- Drill bit may cut oversize



Size	Item #	Barcode	Price
6.0	148010006	9311744435104	
8.0	148010008	9311744435111	
10.0	148010010	9311744435128	
12.0	148010012	9311744436811	
15.0	148010015	9311744436828	
20.0	148010020	9311744436835	
25.0	148010025	9311744436842	

Product Group: C0408

TCT Ceramic Tile Holesaws

TCT Ceramic Tile Holesaws

For superior performance on chipboard, timbers, ceramic tiles and fibreglass.

Helpful Hints

- Use HSS pilot drill for timbers, chipboard and fibreglass
- Select masonry pilot drill for most ceramic tiles and cement sheeting.
- Scratch tile glaze where pilot drill is to make contact prior to drilling.
- Do not use with hammer action



Size	Shank Size	Pieces	Item #	Barcode	Price
Holesaws: 29mm, 38mm, 44mm, 57mm	11/32 Hex (10mm Chuck)	6	9109700	9311744435692	
Arbors: 6519					
Adapter: 237B05511 - used with 29mm holesaw					
Pilot Drills: 1 x HSS Pilot Bit , 1 x Carbide Tipped Pilot Bit (for use in cement sheeting)					

Sutton Tools Pty Ltd ABN 12 004 175 731
100% Australian Owned Company

Head Office 378 Settlement Road, Thomastown 3074, Victoria Australia
T +61 3 9280 0800 **F** +61 3 9464 0015 **E** sutton@sutton.com.au

Customer Service
T 1800 335 350 **F** 1800 333 127 **E** cservice@sutton.com.au

Special Sales
214 Coleraine Road, Hamilton 3300 Victoria Australia
T 1800 035 010 **F** 1800 804 084 **E** specsales@sutton.com.au

www.sutton.com.au

499980070_0610

